

# ADA404REFSSTBC



32" x 20.25" x 22.5" (H x W x D)

Built-in undercounter ADA compliant +2°C to +8°C all-refrigerator with white cabinet and stainless steel door, pure copper towel bar handle, lock, digital controls, wire shelving, hospital cord with 'green dot' plug, factory installed access port, and automatic defrost operation

### Highlights:

Just 32" high for an easy fit under lower ADA compliant counters

Flexible design allows built-in or freestanding use in 21" wide spaces

Copper towel bar handle kills microbes in a shorter timeframe than other metals for added safety

### Product Features:

ADA compliant design	32" height allows easy installation under lower ADA compliant counters
Built-in capable	Front-breathing design lets you make the best use of space by installing your appliance under the counter
2 to 8° operation	Designed to safely store select pharmaceuticals and other materials with strict temperature requirements
Copper handle	Naturally antimicrobial, the towel bar handle made from pure copper helps to protect against microbes for added safety and cleanliness
Factory-installed lock	Located towards the top of the door for easy access and to provide added security of unit (2 keys included)
Access port	Unit comes with a factory installed probe hole for users to connect their own monitoring equipment
Adjustable digital thermostat	Electronic controls located in the front kickplate for easy & intuitive temperature management, with a readout in Fahrenheit or Celsius
Adjustable wire shelves	Four wire shelves provide optimal storage and improved air circulation in the 3.32 cu. ft. interior

3" thick door Improved insulation for an efficient performance

## ADA404REFSSTBC Specifications:

Overview	
Nominal Height	32.0" (81 cm)
Height of Cabinet	31.75" (81 cm)
Height to Hinge Cap	32.0" (81 cm)
Nominal Width	21.0" (53 cm)
Width	20.25" (51 cm)
Nominal Depth	23.0" (58 cm)
Depth	22.5" (57 cm)
Depth with Handle	25.0" (64 cm)
Depth with door at 90°	40.25" (102 cm)
Capacity	3.32 cu.ft. (94 L)
Defrost Type	Automatic
Door	Stainless Steel
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	1.1
Voltage/Frequency	115 V AC/60 Hz
Weight	69.0 lbs. (31 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101077758
Refrigerator Features	
Door Swing	RHD
Reversible	Yes
Shelf Type	Wire
Shelf Qty	4
Thermostat Type	Digital
Fan Type	Interior
Refrigerant Type	R600a
Refrigerant Amount	0.99oz.
High Side PSI	180.0
Low Side PSI	80.0
Level Legs Qty	2
Interior Light	Yes
Temperature Range	2 to 8°C
Dimensions	
Interior Height	23.5" (60 cm)
Interior Width	16.25" (41 cm)

Interior Depth	17.0" (43 cm)
Compressor Step Height	6.25" (16 cm)
Compressor Step Width	16.25" (41 cm)
Compressor Step Depth	6.0" (15 cm)

