

FF28LWHTBC



24.88" x 18.5" x 17.75" (H x W x D)

Compact all-refrigerator with automatic defrost, pure copper handle, front-mounted lock, and white finish

Highlights:

Copper towel bar handle kills microbes in a shorter timeframe than other metals for added safety

Compact size is ideal for use on top of counters

Save time and energy with low maintenance automatic defrost

Product Features:

Copper handle	Naturally antimicrobial, the towel bar handle made from pure copper helps to protect against microbes for added safety and cleanliness
Automatic defrost	Reduced maintenance with auto defrost system
Compact dimensions	Ideal size for countertop use
Fully finished cabinet	Allows the refrigerator to be used as a freestanding model
Factory installed lock	Keyed lock for secure interior
Adjustable shelving	Includes one full-width adjustable wire shelf and one removable half shelf that can be positioned above the compressor step
One piece interior liner	Easy clean-up with a one piece liner that won't hold a mess in hidden crevices
Right hand door swing	For this unit with the door opening from the other side, add option "LHD"
Adjustable thermostat	Manage the temperature with ease and accuracy

FF28LWHTBC Specifications:

Overview	
Nominal Height	25.0" (64 cm)
Height of Cabinet	24.5" (62 cm)
Height to Hinge Cap	24.88" (63 cm)
Nominal Width	19.0" (48 cm)
Width	18.5" (47 cm)
Nominal Depth	18.0" (46 cm)
Depth	17.75" (45 cm)
Depth with Handle	20.25" (51 cm)
Depth with door at 90°	34.5" (88 cm)
Capacity	2.4 cu.ft. (68 L)
Defrost Type	Automatic
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.7
Voltage/Frequency	115 V AC/60 Hz
Weight	40.0 lbs. (18 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101073361

Refrigerator Features	
Door Swing	RHD
Reversible	Factory Reversible
Shelf Type	Wire
Shelf Qty	2
Adjustable Shelves	Yes
Thermostat Type	Dial
Refrigerant Type	R600a
Refrigerant Amount	0.7oz.
High Side PSI	120.0
Low Side PSI	70.0
Level Legs Qty	2
Temperature Range	35°F to 50°F; for a tighter range, contact our product specialists

Dimensions	
Interior Height	21.5" (55 cm)
Interior Width	16.0" (41 cm)
Interior Depth	13.5" (34 cm)
Compressor Step Height	7.75" (20 cm)
Compressor Step Width	16.0" (41 cm)
Compressor Step Depth	5.0" (13 cm)

